



ESCORTS
AGRI MACHINERY

FARMTRAC

30

PARAMETERS	FARMTRAC 30 4WD
ENGINE	
Power at Rated ERPM, HP (KW)	28.5 HP @ 2800
Type - NA/ TC/TCI/CRDI	NA
Swept Volume (cc)	1318
No of Cylinders	3
Bore x Stroke	83x92
Max. Torque, Nm (+/- 100-200 rpm)	80.5 @ 1800 ERPM
PTO	
PTO speed- Std.	Rear - 540 & 540E
PTO RPM @ Engine RPM	540 @ 2504 / 540E @ 2035
TRANSMISSION	
Type	Hydrostatic
No. of Gears	3 Range
Rear Axle Reduction Type	Bull Gear
Differential Lock	Yes
CLUTCH	
Type	NA
BRAKES	
Type	Oil Immersed Brakes
Hand Brake	Independent
3-POINT LINKAGES	
3 point linkage (Geometry) category I / II	Cat IN
HYDRAULICS	
Functions	Draft & Position Control
Type & Lift Capacity (Kg)	750 Kg (at horizontal position)
Auxiliary Valve	1DA (2 nos.)
STEERING	
Steering	Power Steering
FRONT AXLE	
Front Axle	4WD
TYRE	
Front Tyre	23x8.50-12
Rear Tyre	33x15.5-16.5
VEHICLE	
Air Cleaner type	Dry Air Cleaner
CAPACITIES (+/-5%)	
Fuel Tank capacity, ltr.	24
DIMENSIONS (+/-5%)	
Length, mm	2700 (w/o tpl)
Width, mm	1000
Height, mm	2100 (upto steering wheel)
Wheelbase, mm	1550
Ground Clearance, mm	295
Weight, kg (Unballasted)	~1050
OTHER FEATURES	
	Downdraft Exhaust ROPS Engine Shut-off with Key Battery Cut-off Switch Swinging Draw Bar
OPTIONAL FEATURES	
	Agriculture Tyres Industrial Tyres

Due to technical upgrades & modifications, technical data may vary from stated figures.