



SPECIFICATIONS

DESCRIPTION	FT-6065	FT-6060
Engine	4 Cylinder Turbo Intercooled	4 Cylinder Turbo Intercooled
Engine Power (Ps)	65	60
Rated RPM	2200	2000
Max. Torque (Nm)	260 Nm @ 1400rpm	253 Nm @ 1400 rpm
FIP	Inline	Inline
Torque Backup	20%	20%
PTO	540	540
Transmission	Synchromesh	Synchromesh
Drive	4 WD	2WD
Gear	12 Forward 12 Reverse	12 Forward 12 Reverse
Rear Drive	Epicyclic	Epicyclic
Hydraulic Lift	ADDC	ADDC
Lift Capacity	2400 kg	2400 kg
Hydraulic Pump Capacity	18.0 cc	18.0 cc
Clutch	Independent Clutch	Independent Clutch
Disc Material	Cermetallic Disc	Cermetallic Disc
Brakes	Multi-plate Oil Immersed Brakes	Multi-plate Oil Immersed Brakes
Steering	Power Steering	Power Steering
Front Axle	Indegenous 4WD	Adjustable
Front Tyre	11.2x24, 8 PR	7.5 x 16, 8 PR
Rear Tyre	16.9x28, 12 PR	16.9x28, 12 PR
Others		
3-Point Linkage	Pin Type Staybar	Pin Type Staybar
Seat	Adjustable Deluxe	Adjustable Deluxe
Air Cleaner Type	Dry Type with Clogging Sensor	Dry Type with Clogging Sensor
Transport Lock	Yes	Yes
Auxiliary Valve	Yes	Yes
Safety Start Switch Neutral	Yes	Yes
Shifting Pattern	Side Shift	Side Shift
Flat Backend	Yes	Yes
Differential Lock	Yes	Yes
Fuel Tank Capacity, ltrs (Min)	60	60

Note : The above specifications & features may change as part of our efforts on continuous product development.

FARMTRAC Series

***Available in Tier II & Euro II Emission.
European Homologated.**



See your local contact



Agri Machinery Group
Escorts Limited
 Plot No. 2, Sector-13, Faridabad -121007
 Haryana (INDIA)
 Phone : 0129-2575507 / 5292