



TRACTOR	FARMTRAC 6090 Pro 4WD	FARMTRAC 6090 X Pro 4WD
ENGINE		
HP Category	90 HP @ 2200 RPM	90 HP @ 2200 RPM
Type - NA/ TC/TCI	TCI	TCI
Swept Volume (cc)	3680	3680
No of Cylinders	4	4
PTO		
PTO speed- Std.	540/540E & Ground PTO (Independent type)	540/540E & Ground PTO (Independent type)
PTO RPM @ Engine RPM	540 @ 1938 / 540E @ 1648	540 @ 1938 / 540E @ 1648
TRANSMISSION		
Type	Synchromesh	Synchromesh
No. of Gears	12F+12R	12F+12R
Rear Axle Reduction Type	Epicyclic	Epicyclic
Differential Lock	Yes	Yes
CLUTCH		
Type	Double Clutch	Double Clutch
BRAKES		
Type	Oil Immersed Brakes	Oil Immersed Brakes
3-POINT LINKAGES		
3 point linkage (Geometry) category I / II	Cat II	Cat II
HYDRAULICS		
Functions	Draft & Position Control	Draft & Position Control
Type & Lift Capacity (Kg)	2500 Kg	3000 Kg
Auxiliary Valve	2DA/2SA (4 nos.)	2DA/2SA (4 nos.)
STEERING		
Steering	Power Steering	Power Steering
TYRE		
Front Tyre	12.4X24	12.4X24
Rear Tyre	18.4X30	18.4X30
DIMENSIONS/CAPACITIES (+/-5%)		
Length, mm	4190	4190
Width, mm	1940	1940
Height, mm	2550	2550
Fuel Tank capacity, ltr.	85	100
Other Features		
	With ROPS & Canopy Flat Platform Battery Cut-off switch	With ROPS & Canopy, Tilttable Steering Flat Platform with dampers and well suitable for mounted cabin Smart Lift, Engine shut off with Key & Battery Cut-off switch
Optional Features		
	3000 Kg Lifting Capacity Creeper Transmission 12.4*24 & 13.6*38 - Row Crop Tyres 320/85 R24 & 460/85 R30 Radial Tyres 12.4*24 & 18.4*30 - R2 Tyres	Creeper Transmission Semi-Automatic Hitch 12.4*24/13.6*38 - Row Crop Tyres 320/85 R24 & 460/85 R30 Radial Tyres 12.4*24 & 18.4*30 - R2 Tyres